

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

**Defective images within this document are accurate representation of
The original documents submitted by the applicant.**

Defects in the images may include (but are not limited to):

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORLED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

Serial No 09/6017784
Group No 3737



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 :

A61N 1/04, 1/32, A61H 39/00

A1

(11) International Publication Number:

WO 93/23112

(43) International Publication Date:

25 November 1993 (25.11.93)

(21) International Application Number: PCT/SE93/00287

(22) International Filing Date: 5 April 1993 (05.04.93)

(30) Priority data:
9201453-9

8 May 1992 (08.05.92) SE

(71)(72) Applicant and Inventor: SCHOUENBORG, Jens [SE/
SE]; Rudeboksvägen 397, S-226 55 Lund (SE).


(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö
(SE).

(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CZ,
DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU,
MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE,
SK, UA, US, VN, European patent (AT, BE, CH, DE,
DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML,
MR, NE, SN, TD, TG).

Published

With international search report.
In English translation (filed in Swedish).

(54) Title: MEDICAL DEVICE



(57) Abstract

A device and a method for relieving chronic and acute states of pain as well as itch, for affecting the motoractivity of disabled people, or for increasing the flow-through of blood in underlying tissue are disclosed. The device comprises a shapable electrode plate (1) through which extend a plurality of electrodes (2) fixed in the electrode plate (1) and terminating, at their respective free ends, in an electrode tip portion (7) for skin penetration, (a) the electrode tip portion (7) of each electrode (2) being surrounded, at a distance of about 0.1-2.0 mm from the electrode tip (8), by a stop means (9) which separates the electrode plate (1) from the skin portion (10), (b) the electrodes (2) cooperating with a collector electrode (6) of opposite electrical polarity to the electrodes (2), and (c) the electrodes (2) and the collector electrode (6) being electrically connected to a control unit (4) designed to activate the electrodes (2) consecutively, so that when pressure is applied on the electrodes (2), the electrode tip portions (7) will penetrate the isolating outer layers of the epidermis in order to stimulate the receptors of the skin. The use of the device is also disclosed.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TC	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

MEDICAL DEVICE

The present invention relates to a device and a
5 method for relieving chronic and acute states of pain as
well as itch, for affecting the motor activity of disabled
people, or for increasing the flow-through of blood in
underlying tissue. The device comprises a shapable elec-
trode plate through which extend a plurality of electrodes
10 which are fixed in the electrode plate and terminate, at
their respective free ends, in an electrode tip portion
for skin penetration. The invention also concerns the use
of the device for relieving chronic and acute states of
pain as well as itch, for affecting the motor activity of
15 disabled people, or for increasing the flow-through of
blood in underlying tissue.

It is well-known that the activation of sensitive
mechanoreceptors in the skin may relieve pain as well as
itch, and quite a number of theories trying to explain the
20 underlying mechanisms have been launched in the past 25
years. The most well-known theory, the gate theory (Melzack
and Wall, Science, 150:971-979, 1965), describes in great
detail how the interaction between mechanoreception and
pain might work. On the basis of this theory, apparatus for
25 transcutaneous electrical nerve stimulation (TENS) were
developed in the 70s and 80s to provide pain relief. These
apparatus activate whole nerves (nerve fibre bands) from
the skin and the underlying tissue. By using a suitable
current intensity, thick myelinated nerve fibres from
30 sensitive mechanoreceptors can be preferentially stimu-
lated, having the lowest threshold for electrical stimula-
tion. This method has been found to have analgetic effects
for some states of pain in about 50% of the patients
tested.

35 The majority of nociceptors (injury receptors) have
slowly transferring non-myelinated axons, so-called C
fibres. These are believed to play a crucial part in

chronic states of pain. Previously, one was labouring under the misapprehension that the pain paths activated by these fibres have a diffuse topographic organisation. However, more recent neurophysiological studies have shown that the pain paths have a very detailed organisation with well-defined activating and inhibiting skin areas (Schouenborg, J. Physiol, 356:169-192, 1984; Schouenborg and Kalliomäki, Exp. Brain Res. 83:67-78, 1990). If effective pain relief is to be achieved, local inhibitory skin areas should thus be specifically stimulated. Established TENS technique does not provide this possibility, since whole nerves from the skin as well as the underlying tissue are stimulated. In addition, the different peripheral nerves practically never supply functionally defined areas.

Studies of the organisation of the pain paths have shown that pain-activated nerve cells, as well as other nerve cells receiving information from the body surface, can be maximally activated from very small areas of the skin. Consequently, it is unnecessary, and probably wrong, to stimulate whole nerves supplying large receptor beds. By consecutively stimulating different nearby points at a low frequency for each point, one might obtain high-frequency activation of central nerve cells without tiring individual inward-leading nerve fibres and central synapses.

The knowledge of central nerve paths mediating itch is quite limited. Itch makes one want to scratch the skin, providing a certain relief. Regrettably, scratching often worsens the itch in the long run by injuring the tissue. Thus, it is desirable to activate the central itch-relieving mechanisms without injuring the skin.

Recent research has also revealed that individual muscles can be activated and inhibited from specific skin areas. The areas activating a given muscle correspond to those areas of the skin that the muscle removes upon contraction, and the areas inhibiting a given muscle correspond to those areas of the skin that are moved by the muscle towards a stationary object upon contraction.

Muscular activity might be controlled by specifically activating these areas of the skin. This is of importance in order to facilitate motor activity or alter involuntary motor activity under various disabling conditions.

5 The object of the present invention is to provide a device and a method enabling specific stimulation of the receptors in the skin in order to relieve chronic and acute states of pain as well as itch, affect the motor activity of disabled people, or increase the flow-through of blood
10 in underlying tissue.

This object is achieved by a device and a method which are of the type indicated by way of introduction and which in addition exhibit the features recited in the characterising clauses of the appended claims. Preferred embodiments
15 of the invention are defined in the subclaims.

The inventive device differs from existing TENS apparatus by the stimulation being performed locally within a defined and functional area of the skin, TENS stimulating whole nerves which convey unspecific information from the
20 skin as well as the underlying tissue. Since stimulation from multiple points can be performed consecutively, thus reaching individual skin receptors at a relatively low frequency, fatigue phenomena (accommodation) of individual inward-leading nerve fibres and their central synapses can
25 be reduced. TENS, on the other hand, activate whole nerves, and consequently a large number of nerve fibres, which involves a pronounced fatigue phenomenon.

Furthermore, TENS generates an unpleasant sensation of current owing to the synchronous activation of nerve
30 fibres. This sensation often radiates along the distribution of the stimulated nerves.

The inventive device, on the other hand, initially gives rise to a local and brief pricking pain which largely can be eliminated by gradually increasing the intensity of
35 the stimulation. In addition, the inventive device makes it possible to use a lower current intensity (6 mA at the most) than in TENS (30-60 mA). The voltage used in the in-

vention (40 V at the most, usually below 20 V) is also much lower than that used in TENS (50-200 V). This reduces the risk of complications, e.g. for people with pacemakers.

Moreover, the present invention differs from acupuncture in the following way. In acupuncture, the skin is punctured by individual needles which penetrate the underlying tissue. Stimulation is brought about either by electrical current or by mechanical manipulation. Since the needles used are not insulated, current dissipates along the needles, resulting in an unspecific stimulation of receptors in the skin as well as deeper-lying tissue. Often, acupuncture also activates nearby nerves passing by. Thus, acupuncture differs from the present invention primarily by providing unspecific stimulation of different types of receptors along the needle and nearby nerves. Furthermore, the current intensity used in acupuncture is, as a rule, higher than that used in the invention.

US patent 3,612,061 (Collins et al) relates to a flexible electrode matrix. The aim of this invention is to use the tactile sense of blind people for transmitting information. The US device consists of a flexible sheet or plate with electrodes placed in a matrix. Each electrode is connected to a separate, lying cable to a power supply unit. The sheet is earthed. The electrodes can be individually stimulated, and the electrode matrix may therefore be stimulated according to different patterns. Each electrode projects from the sheet and consists of a cylinder having a convex surface which is applied to the skin under pressure. Among other things, the US device differs from the present invention in that the electrodes do not penetrate the skin. No parameters for the stimulation are indicated. However, the electrodes are apparently not intended to be stimulated consecutively, a spatial pattern being aimed at. Since the electrodes do not penetrate the skin, a higher voltage is needed for stimulating the skin receptors/nerves. As a result, the current dissipates to a larger extent and is less specific than in the present invention.

US patent 4,982,743 (Pierson) relates to an itch reducer, which comprises an electrode sheet or plate (smaller than 4 cm²) having projecting and blunt electrodes to be applied against the skin. The electrodes project 0.2-1.0 mm from the sheet. However, the electrode tips are not pointed and are only pressed slightly into the skin when the electrode head is applied against the skin surface. The US specification explicitly states that the electrodes do not penetrate or perforate the skin. The skin is stimulated by direct voltage (20 V at the most) for up to a minute or so. It is further indicated that the stimulation is not felt (i.e. does not noticeably activate the skin receptors) while the itch is relieved. The US itch reducer differs from the present invention in that the electrodes, as already stated, are not designed to penetrate the skin. Furthermore, direct current is used, and not pulsed stimulation. Unlike the inventive device, the US device does not provide any possibility of consecutively stimulating the different projecting electrodes. Finally, the size of the sheet is even smaller than 4 cm².

EP-A-0,377,057 (Bernardini et al) relates to a hand-operated electromedical device for analgetic skin treatment, more precisely a portable apparatus having four electrode pairs embedded in a plate. The electrodes, which are blunt and shown as round in the accompanying drawing, do not penetrate the skin. The electrode pairs are stimulated at the same frequency. Any parameters for the stimulation are not indicated, neither are the dimensions of the apparatus. The EP apparatus differs from the inventive device in that the electrodes do not penetrate the skin and in that only a few electrode pairs are used. Further, it is not possible to stimulate these electrodes consecutively. The stimulation voltage should, in addition, be much higher in order to activate receptors/nerves, as in conventional TENS. Moreover, the current density does not become as high intracutaneously.

The state of the art is further disclosed in EP-A-0,249,532 (Ory), US patents 4,982,742 (Claude), 4,509,535 (Bryan), 4,453,548 (Maurer et al) and 4,823,810 (Dervieux), as well as US patents 4,708,149, 4,722,354, 4,867,166 and
5 5,038,796 (all to Axelgaard and Grussing). The devices taught by these publications all have in common that no penetration of the skin by electrodes takes place, and the mechanoreceptors and pain receptors of the skin can therefore not be specifically stimulated. Furthermore, none of
10 these devices enables consecutive stimulation.

The invention will be described in more detail below with reference to the accompanying drawings, in which

Fig. 1 is a side view of a preferred embodiment of the inventive device;

15 Fig. 2 is a section of an electrode arranged in the electrode plate of the device shown in Fig. 1;

Fig. 3 is a section of four different embodiments of the electrode tip portion and the stop means according to the invention; and

20 Fig. 4 is a section in perspective of a skin portion.

As appears from Fig. 1, an electrode plate 1 is provided with several electrodes 2 fixed in the plate 1 and extending therethrough. Each electrode 2 is connected to a control unit 4 by an electric line 3. The control unit 4 is
25 in turn connected, by an electric line 5, to a collector electrode 6 of opposite electrical polarity to the electrodes 2. The electrode plate 1 with the electrodes 2 projecting from its underside, and the collector electrode 6 are applied to a skin portion 10 during the stimulation
30 operation.

Preferably, the electrode plate 1 is shapable and substantially flat. The plate may be of different size, depending on the size of the skin portion to be stimulated. Further, the plate is made of some conventional pliable material enabling it to be used on curved parts of the body,
35 such as the elbows, the shoulders and the knees. The plate may be about 1-500 cm², but preferably is about 4-300 cm².

Naturally, the size of the plate depends on the skin area to be stimulated. Where the skin has low receptor density, fairly large areas have to be stimulated. For instance, comparatively large areas are stimulated on the back and the back of the head, while smaller areas are stimulated on the arms and the face. If need be, one or more electrode plates 1 may in addition be connected when large areas of the skin are to be stimulated. Electrically, the electrode plate 1 may be an insulator in its entirety or it may be made up of an insulator in the layer closest to the skin and, in an overlying layer, consist either of electrically conductive wires from the electrodes 2 to the control unit 4 or of printed board. In a preferred embodiment, the electrode plate 1 is a sleeve of silicon rubber.

Electrodes 2 extend through recesses in the electrode plate 1 and project from the underside of the plate facing the skin portion 10, as shown in Fig. 2. The electrodes 2 are substantially elongate and are made of conventional conductive material. By an electric line 3, the upper end of each electrode 2 is connected to the control unit 4. This upper end may project from the upper side of the electrode plate 1 facing away from the skin portion or it may be embedded in the electrode plate 1. At the lower end, the electrode 2 ends in an electrode tip portion 7 intended to penetrate the skin portion 10. It is of considerable importance that the electrode tip portion 7 is so designed that it can penetrate the skin sufficiently to achieve the desired stimulation of the skin receptors. The electrode tip portion 7 is pointed at an angle less than 90° , preferably less than 45° . The electrode tip portion 7 may be perfectly conically pointed or convexly/concavely conically pointed or it may have a cutting edge. It may also be otherwise designed, provided that it meets the requirements at issue, and thus may have the shape of a needle or a pin.

The cross-sectional surface of the electrode tip portion 7 can also be so small that the skin is penetrated under the exertion of a pressure, regardless of its design. The

cross-sectional surface should be about 1 mm^2 at the most, preferably 0.25 mm^2 at the most, in order to minimise skin injuries caused by the penetration.

To achieve controlled penetration, a stop means 9 is furthermore provided round the projecting lower electrode part formed with the electrode tip portion 7, in such a manner that it also surrounds the electrode 2 and serves as a spacer between the underside of the electrode plate 1 and the skin portion 10. This also creates an air gap 11 between the electrode plate 1 and the skin portion 10. The term "electrode tip portion" is used to designate the portion of the electrode 2 projecting from the stop means 9. The stop means 9 can be made of any conventional material, e.g. either an electrically conductive material or an insulating material, and have any suitable design. Preferably, the stop means is a hollow cylinder with a height of about 0.1-5 mm. Its skin contact surface, which preferably is annular, has a size of about $0.2\text{-}25 \text{ mm}^2$, depending on the electrode density and the curvature of the skin surface. In a preferred embodiment, the skin contact surface of the stop means 9 is about 3 mm^2 . The stop means 9 may be a separate component of the device, but it may also be made in one piece with the electrodes 2. Thus, the stop means 9 enables the electrode 2 to penetrate to a predetermined depth in the skin when pressure is applied from above. Preferably, the lower end of the stop means 9 is convex for optimal skin contact. The skin contact surface may alternatively be flat, be flat closest to the electrode tip portion 7 and rounded up towards the electrode plate 1, or be conical. As appears from Figs 3A-D, showing alternative embodiments of the invention, the angle α between the stop means 9 and the electrode tip portion 7 should not exceed 160° to enable satisfactory control of the penetration depth of the electrode 2 into the skin. In the preferred embodiment, the angle α between the stop means 9 and the electrode tip portion 7 is about 90° . Basically, a device in which the electrode plate 1 in itself serves as stop

means is also conceivable. However, such an arrangement does not enable satisfactory control of the penetration depth of the electrodes 2 into the skin.

Since different receptors are located at different depths in the skin, it is possible to select the group of receptors to be stimulated by varying the penetration depth of the electrode tip portion 7 into the skin. The present invention is preferably used for stimulating receptors in the lower part of the epidermis and the upper part of the dermis. When the electrode 2 is applied to the skin portion 10 under the exertion of a pressure, the electrode tip portion 7 perforates the electrically insulating layers of the epidermis (stratum corneum and stratum lucidum, i.e. the horny layer made up of dead cells of the skin. As appears from Fig. 4, which is a section illustrating the structures and the positions of receptors in the skin, the electrodes 2 should reach down to the lower part of the epidermis 13 and the upper part of the dermis 16, being the location of both nociceptors 14 and sensitive mechanoreceptors 15. The term "receptors" used throughout this description relates to mechanoreceptors and nociceptors as well as their intracutaneous nerve fibres in the layers of the skin 13 and 16. The horny layer 12 constitutes the uppermost part of the epidermis 13. When the electrode tip portion 7 passes these layers of the skin, the electrical resistance between the electrode tip and the receptor is considerably reduced. The voltage and the current intensity required for activating receptors in the skin may therefore be considerably reduced as well. The skin penetration depth, i.e. the vertical distance between the tip 8 of the electrode tip portion 7 and an imaginary extension of the surface of the stop means 9 applied against the skin portion 10, depends on the type of skin to be stimulated and on how far into the skin stimulation is to take place. The electrode tip portion 7 preferably projects about 0.1-2.0 mm, in a particularly preferred embodiment about 0.2-1.2 mm. The term "skin penetration", used throughout the

description and the claims, encompasses penetration through the skin layers to the sensitive mechanoreceptors 15 and the nociceptors 14 found in the lower part of the epidermis 13 and the upper part of the dermis 16.

5 The electrodes 2 can be arranged at different distances from the electrode plate 1. For practical reasons, however, distances above about 30-50 mm and below about 2-5 mm should not be used. The number of electrodes 2 per electrode plate 1 may vary between about 2 and 100, and preferably is about 15-50. However, an electrode plate 1 having but a single electrode might also be used. In that case, pain relief would be more limited than when using the preferred embodiment with multiple electrodes. The electrodes 2 can be asymmetrically arranged on the electrode plate 1, depending on the skin portion to be treated. The above parameters are easily determined by anyone skilled in the art.

15 In a preferred embodiment of the invention, the plate is oval or rectangular and has a surface area of about 100 cm², 16 electrodes being symmetrically arranged on the plate and spaced apart 20 mm. In the preferred embodiment, the electrodes 2 are in addition cylindrical and have a diameter of about 0.5 mm.

20 In the preferred embodiment, the electrode plate 1 consists of an upper layer having integrated lines/printed boards and a lower insulator layer. The stop means 9 is made in one piece with the electrodes 2.

25 The control unit 4, which is connected to each electrode 2 on the electrode plate 1 by electric lines 3, utilises conventional electronics and is designed to provide the required values of the electronic parameters used in the invention. The control unit 4 may be either enclosed in a separate container or encased directly on the electrode plate 1. In the preferred embodiment of the invention, the electrodes are activated consecutively, i.e. in turn, to achieve optimal effect. Although simultaneous stimulation of all the electrodes is possible, this does

11

not yield as good results. With the aid of the control unit 4, the frequency for each electrode 2 can be varied between about 1 Hz and 300 Hz, preferably between about 5 Hz and 100 Hz, but is about 40 Hz in a preferred embodiment. The voltage and the current intensity required for activating the receptors in the skin can, according to the invention, be reduced to about 40 V and about 6 mA, at the most, preferably to about 20 V and about 3 mA, at the most. In the preferred embodiment, the voltage does not exceed about 15 V and the current intensity does not exceed about 1-3 mA. When using the inventive device for pain and itch relief, the voltage is gradually increased during a first period lasting about 5-10 min, which considerably reduces any feeling of discomfort as compared with the discomfort felt when the stimulation voltage is increased stepwise to the required level. Stimulation then continues for about 20-50 min, but more time may be needed for some states of pain. The required pulse duration is about 0.01-5 ms, preferably 0.2-1 ms, and is 0.2 ms in a preferred embodiment. The above parameters depend on which portion of the skin is to be stimulated.

By an electric line 5, the control unit 4 is connected to a shapable, electrically conductive collector electrode 6, which is an electrode of opposite polarity to the electrodes 2. The collector electrode 6 is made of conventional material and may, like the electrode plate 1, be adjusted to curved body surfaces when need be. The shape and surface of the collector electrode 6 can be varied to a considerable extent, and the surface area is about 15-25 cm² in a preferred embodiment. When using the inventive device, the required current transfer takes place between the electrodes 2 and the collector electrode 6 of opposite polarity. The collector electrode 6 can be applied to the skin portion 10 at a distance from the electrode plate 1 or be applied as a frame round the plate. The collector electrode 6 may also be otherwise positioned in relation to the electrode plate 1.

Thus, the electrodes 2 can be either cathodes or anodes. When the electrodes 2 are cathodes, the collector electrode 6 is an anode, and vice versa. In a preferred embodiment of the invention, the electrodes 2 are cathodes and the collector electrode 6 is an anode.

In another embodiment of the invention, the electrodes 2 on the electrode plate 1 can operate in pairs as cathode and anode. Alternatively, groups of two or more electrodes 2 on the electrode plate 1 can act as mutual cathode-anode pairs with another group of electrodes 2 on the electrode plate 1. In this embodiment, the collector electrode 6 is superfluous and thus dispensed with.

The inventive device can be applied to the skin portion 10 at issue with the aid of a conventional fixing device (not shown), such as a sleeve with an adjustable clamping means, or with the aid of tissue adhesive. It is of great importance that the electrode plate 1 with the electrodes 2 and their electrode tip portions 7 can be applied against the skin portion at issue by adjustable pressure exertion to achieve the skin penetration required.

The present invention further concerns a method for relieving chronic and acute states of pain as well as itch, for affecting the motor activity of disabled people, or for increasing the flow-through of blood in underlying tissue, in which method a) a device according to the invention is applied with pressure against the skin portion to be stimulated, the electrode tip portions 7 of the electrodes 2 penetrating the skin portion 10 and reaching the area of the receptors; and b) the electrodes 2 are activated consecutively by the control unit 4 at a frequency of about 1-300 Hz, a current intensity not exceeding about 6 mA and a pulse duration of about 0.01-5 ms for a stimulation period of up to about 1 h.

The present invention also relates to the use of the inventive device for relieving chronic and acute states of pain as well as itch, for affecting the motor activity of disabled people, or for increasing the flow-through of

13

blood in underlying tissue. The inventive device may also be used for more than one of these applications at the same time.

With the aid of the invention, it is thus possible to affect also the motor activity of disabled people whose muscles are partly or totally paralysed. Normally, the current intensity then is not gradually increased for 5-10 min. In such an instance, the skin area is stimulated in a manner coordinated with the intended motor activity.

Furthermore, the flow-through of blood in underlying tissue can be locally increased by stimulation with the aid of the device according to the invention. Such an increase in the blood flow has been shown, inter alia by an increase in temperature in the treated area of the skin.

Evaluation of the Analgetic and Itch-relieving Effects of the Invention

In a test involving 6 patients, pronounced and local pain relief in the stimulation area occurred within 3-5 min. The pain caused by heat stimulation of the skin surface showed that the pain threshold had been considerably raised. As a rule, the feeling of pin pricking disappeared completely. Moreover, tests on 4 patients with back muscle pain and tennis elbow showed good and long-term pain relief lasting several days.

In addition, the inventive device totally blocked itch, caused by an injection of histamine, in 3 patients and considerably relieved the itch in another 3 patients after about 5 min. of stimulation. The effect lasted more than 1 h.

30

35

CLAIMS

1. A device for relieving chronic and acute states of
5 pain as well as itch, for affecting the motor activity of
disabled people, or for increasing the flow-through of
blood in underlying tissue, said device comprising a shap-
able electrode plate (1) through which extend a plurality
of electrodes (2) which are fixed in the electrode plate
10 (1) and terminate, at their respective free ends, in elec-
trode tip portions (7) for skin penetration, c h a r a c -
t e r i s e d in that

(a) the electrode tip portion (7) of each electrode
(2), at a distance of about 0.1-2.0 mm from the electrode
15 tip (8), is surrounded by a stop means (9) separating the
electrode plate (1) from the skin portion (10),

(b) the electrodes (2) cooperate with a collector
electrode (6) of opposite electrical polarity to the
electrodes (2), and

20 (c) the electrodes (2) and the collector electrode (6)
are electrically connected to a control unit (4) designed
to activate the electrodes (2) consecutively, so that when
pressure is applied on the electrodes (2), the electrode
tip portions (7) will penetrate the isolating outer layers
25 of the epidermis to stimulate the receptors of the skin.

2. A device as claimed in claim 1, c h a r a c -
t e r i s e d in that the electrodes (2) are cathodes, and
that the collector electrode (6) is an anode.

3. A device as claimed in any one of the preceding
30 claims, c h a r a c t e r i s e d in that the control
unit (4) is designed to activate the electrodes (2) con-
secutively at a frequency of about 1-300 Hz, a current
intensity not exceeding about 6 mA, and a pulse duration of
about 0.01-5 ms.

35 4. A device as claimed in claim 3, c h a r a c -
t e r i s e d in that the control unit (4) is designed to
activate the electrodes (2) consecutively at a frequency of

15

preferably about 5-100 Hz, a current intensity not exceeding about 3mA, and a pulse duration of about 0.2-1.0 ms.

5 5. A device as claimed in any one of the preceding claims, characterised in that the electrode plate (1) has a surface area of 4-300 cm², and that 2-100 electrodes (2) are fixed in the electrode plate (1).

10 6. A device as claimed in any one of the preceding claims, characterised in that the electrode tip portion (7) of each electrode (2) is pointed, has a cutting edge or so small a cross-sectional surface that the skin portion (10) is penetrated, regardless of the design of the electrode tip (8), and that the electrode tip portion (7) is surrounded by the stop means (9) at a distance
15 of about 0.2-1.2 mm from the tip (8).

20 7. A device as claimed in any one of the preceding claims, characterised in that the contact surface of the stop means (9) with the skin is flat, flat closest to the electrode tip portion (7) and rounded up towards the electrode plate (1), or conical, in which case the angle between the electrode tip portion (7) and the stop means (9) does not exceed 160°.

25 8. A device as claimed in any one of the preceding claims, characterised in that one or more electrode plates (1) according to the invention are connected for stimulating a major skin portion.

30 9. A device as claimed in any one of the preceding claims, characterised in that the electrodes (2) in the electrode plate (1), in pairs or groups, form mutual anode-cathode pairs, the collector electrode (6) being excluded from the device.

35 10. A method for relieving chronic and acute states of pain as well as itch, for affecting the motor activity of disabled people, or for increasing the flow-through of blood in underlying tissue, characterised in that

(a) a device, which comprises a shapable electrode plate (1) through which extend a plurality of electrodes (2) which are fixed in the electrode plate (1) and terminate, at their respective free ends, in electrode tip portions (7) for skin penetration, the electrode tip portion (7) of each electrode (2) being surrounded, at a distance of about 0.1-2.0 mm from the electrode tip (8), by a stop means (9) separating the electrode plate (1) from the skin portion (10), the electrodes (2) cooperating with a collector electrode (6) of opposite electrical polarity to the electrodes (2), and the electrodes (2) and the collector electrode (6) being electrically connected to a control unit (4) designed to activate the electrodes (2) consecutively, so that when pressure is applied on the electrodes (2), the electrode tip portions (7) will penetrate the isolating outer layers of the epidermis in order to stimulate the receptors of the skin, is applied with pressure to the skin portion to be stimulated, the electrode tip portions (7) of the electrodes (2) penetrating the skin portion (10) and reaching the area of the receptors, and

(b) the electrodes (2) are activated consecutively by the control unit (4) at a frequency of about 1-300 Hz, a current intensity not exceeding about 6 mA and a pulse duration of about 0.01-5 ms during a stimulation period of up to about 1 h.

11. The use of a device as claimed in claims 1-9 for relieving chronic and acute states of pain as well as itch, for affecting the motor activity of disabled people, or for increasing the flow-through of blood in underlying tissue.

1/2

FIG.1





FIG.2



2/2

FIG.3A




FIG.3B




FIG.3C




FIG.3D





FIG.4



1 INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 93/00287

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: A61N 1/04, A61N 1/32, A61H 39/00
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: A61N, A61H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO, A1, 9005560 (JOSEF, C SZELES), 31 May 1990 (31.05.90), page 4, line 35 - line 37; page 12, line 24 - line 36	1-9
A	US, A, 5058605 (PETR SLOVAK), 22 October 1991 (22.10.91), column 5, line 53 - line 57	1-9
A	US, A, 4254776 (KAZUO TANIE ET AL), 10 March 1981 (10.03.81), column 4, line 26 - line 31; column 5, line 57 - line 65	1-9
A	US, A, 4982743 (MARLIN R. PIERSON), 10 March 1991 (10.03.91), se hela dokumentet	1-9

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principles or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 July 1993

Date of mailing of the international search report

22 -07- 1993

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimil No. +46 8 666 02 86

Authorized officer

Rune Bengtsson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 93/00287

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 4926879 (CHRISTOPHE SEVRAIN ET AL), 8 January 1991 (08.01.91), se hela dokumentet ---	1-9
A	US, A, 5067495 (RICHARD L. BREHM), 26 November 1991 (26.11.91), se hela dokumentet -----	1-9

INTERNATIONAL SEARCH REPORT

International application N.
PCT/SE93/00287

B x I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 10, 11
because they relate to subject matter not required to be searched by this Authority, namely:
a method for treatment of the human or animal body
by surgery or therapy as well as diagnostic methods
Rule 39.1 (iv)
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such
an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all
searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment
of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report
covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is
restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

28/05/93

International application No.

PCT/SE 93/00287

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO-A1-	9005560	31/05/90	AT-B-	395105	25/09/92
			AU-A-	4634089	12/06/90
			EP-A-	0444097	04/09/91
			AT-B-	395106	25/09/92
			JP-T-	4502868	28/05/92
US-A-	5058605	22/10/91	AU-B-	630666	05/11/92
			AU-A-	5003990	30/08/90
			EP-A-	0384430	29/08/90
US-A-	4254776	10/03/81	JP-C-	1103617	16/07/82
			JP-A-	53082980	21/07/78
US-A-	4982743	10/03/91	NONE		
US-A-	4926879	08/01/91	NONE		
US-A-	5067495	26/11/91	NONE		